

Model	Dimensions L*W*H (mm)	Fan	cooling capacity (kcal/h)
10T	900*900*2200	0.37kw*1	50,000
20T	1000*1000*2350	0.75kw*1	100,000
30T	1500*1000*2450	1.5kw*1	150,000
40T	2000*1000*2450	0.75kw*2	200,000
50T	1800*1500*2450	0.75kw*2	250,000
60T	2000*1500*2550	2.2kw*1	300,000
80T	2000*1800*2500	2.2kw*1	400,000
100T	2200*2000*3100	1.5kw*2	500,000
120T	2800*2000*3150	2.2kw*2	600,000
140T	3000*2000*3150	1.5kw*3	700,000
150T	3300*2000*3150	1.5kw*3	750,000
160T	3500*2000*3150	2.2kw*3	800,000
180T	4000*2000*3150	2.2kw*3	900,000
200T	4500*2000*3150	2.2kw*4	1,000,000
250T	4500*2500*3300	3kw*3	1,250,000
280T	5000*2500*3300	3kw*3	1,400,000
300T	4600*3000*3300	2.2kw*6	1,500,000
350T	5500*3000*3500	5.5kw*2	1,750,000
400T	6000*3000*3500	4kw*3	2,000,000
500T	8000*3000*3600	4kw*4	2,500,000

The shell of the square open cooling tower is made of magnesium-aluminum-zinc alloy, which is more durable than fiberglass, has a longer service life, and has recycling value. The filler is made of PVC and can be customized to PP.

It supports customization of larger tonnage, and the size can be customized according to transportation conditions, but it must be done under the premise of ensuring cooling capacity. It supports the installation of water pumps.